Rotary Power Grader

40+ HP SKID STEER







FEATURES

» Hydraulic bidirectional rotor for forward and reverse operation

- » 25 degree angle and 28 degree tilt for easy swaling and ditching
- » Dual-motor design delivers 40% more torque and eliminates outside bearings and chains

REQUIRED FLOW

65 - 110 LPM

MAX WIDTH 2430 mm

SCAN FOR **MORE INFO**



CODE	DESCRIPTION	ANGLE & TILT	FLOW RANGE	WEIGHT	PRICING
RR60UN	1525 mm (60") Rotary Power Grader	Manual Angle & Tilt	65 - 110 LPM	521 kg	GET QUOTE
RR72UN	1830 mm (72") Rotary Power Grader			553 kg	
RR84UN	2130 mm (84") Rotary Power Grader			580 kg	
RR96UN	2430 mm (96") Rotary Power Grader			626 kg	
RR60ATOTFUN	1525 mm (60") Rotary Power Grader	Hydraulic Angle & Tilt (On the Fly)		521 kg	
RR72ATOTFUN	1830 mm (72") Rotary Power Grader			553 kg	
RR84ATOTFUN	2130 mm (84") Rotary Power Grader			580 kg	
RR96ATOTFUN	2430 mm (96") Rotary Power Grader			626 kg	
EWK_PIN	Electric Wiring Harness Kit 8/14 Pin (All makes except Bobcat 7 Pin) Included with Hydraulic Power Grader				
EWK7PIN	Electric Wiring Harness Kit (Bobcat 7 Pin CANBUS)				
RRHTAVK	Hydraulic Angle & Tilt Kit "On the Fly" (Supply Only)				
RRSCK	Rotary Power Grader Side Cutters (SET)				

Rotary Power Grader

GALLERY









