

AG LOADER PUSH STICK RAKE



FEATURES

- » Robust construction with side wings
- » Mounting available for optional Dozer Blade
- » 155 mm spacing between high grade tynes
- » Rear tyne stabilisers and curved front

HEIGHT
900 MM

MAX TYNE SIZE
100 × 25 MM



TAKE A CLOSER LOOK

himac.com.au/apr

CODE	DESCRIPTION	CONSTRUCTION	SUITABILITY	WEIGHT	PRICING
PRM18E	1800 mm Push Rake	100 x 16 mm high grade tynes	40 - 60 HP	275 kg	GET QUOTE
PRM21E	2100 mm Push Rake			310 kg	
PR18E	1800 mm Heavy Duty Push Rake	100 x 20 mm high grade tynes	65 - 140 HP	355 kg	
PR21E	2100 mm Heavy Duty Push Rake			380 kg	
PR24E	2400 mm Heavy Duty Push Rake			415 kg	
PREX24E	2400 mm Extreme Duty Push Rake	100 x 25 mm high grade tynes	150+ HP	480 kg	
GRP	Optional grill protection guard				
PRSG21	Optional Mesh Safety Guard - 600 mm High - Suit 2.1 m				
PRSG24	Optional Mesh Safety Guard - 600 mm High - Suit 2.4 m				
DSRH	Optional dozer blade (HD models only)				



HARD WORK
MADE EASY

1800 888 114

himac.com.au